



 **LONESTAR**  
SILENCER

**HUNTER**  
OWNER'S MANUAL

# THE QUIET CONFIDENCE GUARANTEE

This manual will help you avoid trouble. However, should trouble find you, your silencer is covered by our Quiet Confidence Guarantee. If you ever experience a problem with your silencer—whether caused by us or you—we will make it right.



## SPECIFICATIONS

- **Caliber Rating:** Up to .36 caliber
- **Maximum Cartridge Rating:** Rated up to .300 Norma Magnum
- **Length:** 9.1 inches
- **Diameter:** 1.58 inches
- **Weight:** 23 oz
- **Material:** Stainless steel construction
- **Finish:** Natural stainless or high-temperature Cerakote (model dependent)
- **Mounting:** Direct-thread only
- **Thread Pitch:** 5/8×24 TPI
- **Barrel Restrictions:**
  - Minimum 10.5" barrels for 5.56
  - Minimum 6" barrels for .300 Blackout
  - Minimum 12.5" barrels for .308
  - Minimum 18" barrels for all magnum cartridges
- **Firing Schedule:**
  - Precision / hunting rated; designed for sustained accuracy with reasonable firing cadence. Allow cooling during extended strings.

## WHAT YOU SHOULD HAVE IN THE BOX

- Hunter Silencer
- Owner's Manual

**NOTE:** No adapters or alternate mounting components are included. The Hunter is direct-thread only.

## SAFETY WARNINGS

- Always unload your firearm completely before installing or removing the silencer.
- Ensure the bore is free of obstruction before firing.
- Verify the firearm barrel is threaded **5/8x24 TPI** and properly shouldered.

- Check that threads are clean and free of carbon buildup before installation.
- Do not cross-thread. Hand-tighten only.
- Monitor silencer tightness during use. Stop firing immediately if misalignment, baffle strike, or unusual sound is detected.

## ATTACHING THE SILENCER

### Direct Thread Installation

1. Verify the host firearm is completely unloaded.
2. Inspect both barrel threads and suppressor threads for debris, carbon, or damage.
3. Thread the Hunter directly onto the barrel by hand until it shoulders firmly.
4. Hand-tighten only. Do not use tools, shims, washers, or thread locking compounds.
5. Confirm the suppressor is concentric with the bore before firing.

### IMPORTANT:

The Hunter **is not HUB compatible** and is not designed for quick-detach or secondary mounting systems.

## OPERATING YOUR SILENCER

### Silencer Temperature

Your silencer will absorb significant heat during firing and may become extremely hot. Stainless steel retains heat longer than titanium—allow adequate cooling before handling, removing, or storing.

### Ammunition

We strongly recommend the use of **new, factory-produced ammunition**. Factory ammunition offers consistent pressure and bullet stability. Use of hand-loaded or remanufactured ammunition may increase the risk of baffle strikes or damage and may void performance expectations.

### Hearing Protection

The Hunter significantly reduces muzzle report. However, for extended shooting sessions or high round counts, hearing protection is recommended.



### **Supersonic Crack**

While the Hunter greatly reduces muzzle blast, it cannot eliminate the ballistic crack produced by supersonic bullets. Subsonic ammunition may be used where applicable to further reduce sound signature.

## **CARE AND CLEANING**

- Wipe down the exterior with a light oil and a soft cloth after use.
- Suppressor-safe solvents may be used for internal cleaning if desired.
- Always follow solvent manufacturer instructions to avoid damage.
- Allow the suppressor to dry completely before reuse.
- Routine internal cleaning is not required under normal use.

## **ABLATIVE MEDIA / RUNNING WET**

Do not use ablative media such as water, grease, oil, or gel inside the suppressor. Running the Hunter “wet” is not recommended and may result in unsafe pressure levels, suppressor damage, or personal injury.

## **RETURNS FOR REPAIR**

Your silencer is built for a lifetime of service. If it fails to perform as intended, contact Lone Star Silencer for repair or replacement. Always contact us prior to shipping to ensure proper documentation and compliance with applicable laws.

## **CUSTOMER SERVICE**

Email: [Questions@LoneStarSilencer.com](mailto:Questions@LoneStarSilencer.com)

Phone: (214) 980-5140

Address: 1704 West FM 875, Suite 109, Midlothian, TX 76065

